



**Specifications Multipack 4x Ledvance  
Downlight Slim Alu White 16W 1600lm  
90D - 830 Warm White | Cutout  
175mm - IP44**

[View Product](#)

## General Information

|                          |                                                    |
|--------------------------|----------------------------------------------------|
| SKU                      | 257731                                             |
| EAN                      | 8719157070805                                      |
| manufacturer_code        | 8719157070805                                      |
| Brand                    | Ledvance                                           |
| Manufacturer Name        | Multipack 4x DL SLIM ALU D175 V 16W MS 840 WT LEDV |
| Any Lamp all-in warranty | 5 Years                                            |
| Average Lifetime (h)     | 50000                                              |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Replaces (Watt)             | 2x18              |
| Wattage                     | 16W               |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 830 Warm White    |
| Colour temperature (Kelvin) | 3000 Warm White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |

|                       |                          |
|-----------------------|--------------------------|
| Light Colour Options  | Single Color             |
| Beam Angle (degree)   | 90                       |
| Luminous Flux (Lumen) | 1600lm                   |
| Lumen per watt        | 100                      |
| Power factor          | >0.90                    |
| Unified Glare Rating  | < 23 - for general areas |
| Optical Cover         | Opal                     |
| Product Type Category | LED Downlight            |

## Fixture Information

|                        |                        |
|------------------------|------------------------|
| Mounting Method        | Recessed               |
| Cut out (mm)           | 175                    |
| IP-Rating              | IP44                   |
| Impact Protection (IK) | IK03 - 0.35 joule      |
| Operating Temperature  | -20 to +40             |
| Housing                | Aluminium              |
| Colour of the Fixture  | White                  |
| Fixture Connection     | PI [Push-in connector] |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 23  |
| Diameter (mm) | 187 |

## Why Any-lamp?

## Sensor Information


 Order from the **largest lighting specialist** in Europe


**Customised** quotation


 Up to **7 years warranty**


**Easy** return process